

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 9/2/2021 Revision date: 7/24/2025 Supersedes version of: 6/16/2025 Version: 3.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

 Trade name
 : PUMPKIN PIE #EU13513F

 UFI
 : T5E6-K1SR-H00V-H1FQ

Product code : EU13513F

Type of product : Perfumes, fragrances
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Main use category : Industrial use,Professional use Industrial/Professional use spec : For professional use only

Industrial

Use of the substance/mixture : Perfumes, fragrances Function or use category : Odour agents

#### 1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE INTERNATIONAL GmbH GmbH

Mittlerer Weg 35 DE 79424 Auggen

Germany

T 49-7631-931-8900

SDS@frenchcolor.com, www.frenchcolor.com

#### 1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4

Skin corrosion/irritation, Category 2

H315

Serious eye damage/eye irritation, Category 2

H319

Skin sensitisation, Category 1

Hazardous to the aquatic environment – Acute Hazard,

H400

Category 1

Hazardous to the aquatic environment – Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

#### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

#### Safety Data Sheet

Precautionary statements (CLP)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP) : Warning

Contains : Benzyl benzoate; Cinnamic aldehyde; Eugenol; COUMARIN; Phenylethyl alcohol; Ethyl

maltol; Amyl cinnamic aldehyde; Veratryl aldehyde (Veratraldehyde); Acetyl Propionyl; 1,2-

Cyclopentanedione, 3-methyl-; Benzyl alcohol; beta-Caryophyllene

Hazard statements (CLP) : H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H410 - Very toxic to aquatic life with long lasting effects.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

Extra phrases : For professional users only.

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-	27.5 – 55	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 EC Index-No.: 606-155-00-6 REACH-no: 01-2119935242-	8.51 – 17.0375	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802- 33	3.15 – 6.4	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	2.3795999 – 4.959986625	Eye Irrit. 2, H319
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	1.90002 – 3.80003	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317

# Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Phenylethyl alcohol	CAS-No.: 60-12-8 EC-No.: 200-456-2 REACH-no: 01-2119963921- 31	1.4 – 2.75	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Terpineol	CAS-No.: 8000-41-7 EC-No.: 232-268-1	0.9 – 1.75	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Anisic aldehyde	CAS-No.: 123-11-5 EC-No.: 204-602-6 REACH-no: 01-2119977101- 43	0.884 – 1.675	Aquatic Chronic 3, H412
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	0.5 – 1	Acute Tox. 4 (Oral), H302
Amyl cinnamic aldehyde	CAS-No.: 122-40-7 EC-No.: 204-541-5	0.5 – 1	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Acetyl Propionyl substance with national workplace exposure limit(s) (DE, SI, CH)	CAS-No.: 600-14-6 EC-No.: 209-984-8	0.3 – 0.5	Flam. Liq. 2, H225 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373
1,2-Cyclopentanedione, 3-methyl-	CAS-No.: 765-70-8 EC-No.: 212-154-8	0.3 – 0.5	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	0.3 – 0.5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361 STOT SE 3, H335
benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-38	0.2 – 0.4	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
beta-Caryophyllene	CAS-No.: 87-44-5 EC-No.: 201-746-1 REACH-no: 01-2120745237- 53	0.11 – 0.225	Asp. Tox. 1, H304 Skin Sens. 1B, H317
Veratryl aldehyde (Veratraldehyde)	CAS-No.: 120-14-9 EC-No.: 204-373-2	0.075 – 0.15625	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
.betaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 127-91-3 EC-No.: 204-872-5	0.01 – 0.053	Flam. Liq. 3, H226
.alphaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 80-56-8 EC-No.: 201-291-9	0.01 – 0.053	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
(R)-p-mentha-1,8-diene; d-limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 205-341-0 EC Index-No.: 601-096-00-2 REACH-no: 01-2119493353- 35	0.005 - 0.023	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
p-Cymene substance with national workplace exposure limit(s) (DK, EE, LT, LV, SE)	CAS-No.: 99-87-6 EC-No.: 202-796-7 EC Index-No.: 601-094-00-1	0.001 – 0.01	Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:dust,mist), H331 Repr. 2, H361 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.000762 – 0.0015875	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.00001875	Not classified

Specific concentration limits:			
Name	Product identifier	Specific concentration limits (%)	
Cinnamic aldehyde	EC-No.: 203-213-9	(0.001 < C < 0.01) EUH208 (0.01 ≤ C < 0.1) Skin Sens. 1; H317 (0.1 ≤ C < 100) Skin Sens. 1A; H317	

Full text of H- and EUH-statements: see section 16

### **SECTION 4: First aid measures**

4.1. Description of first aid measures

First-aid measures after eye contact

First-aid measures after ingestion

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical
	advice (show the label where possible). Call a poison center or a doctor if you feel unwell.

		•	•			•
First-aid measures after inhalation	: Remo	ove person to fresh	air and keep	comfortable	for breathing	. Allow affected person to
	broatl	on froch air Allow t	ha victim to	roct		

- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
  - followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
  - : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
  - Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison center or a doctor if you feel unwell.

7/24/2025 (Revision date)	FN (English)	4/37

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Hygiene measures

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

: Wash contaminated clothing before reuse. Contaminated work clothing should not be

allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

7/24/2025 (Revision date) EN (English) 5/37

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container closed when not in use. Store in a well-ventilated place. Keep cool.

Storage temperature : 25 °

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

#### 7.3. Specific end use(s)

No additional information available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

National occupational exposure and biological limit values

Dipropylene glycol monomethyl ether (34590-	Dipropylene glycol monomethyl ether (34590-94-8)		
EU - Indicative Occupational Exposure Limit (IOEL)	EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	308 mg/m³		
	50 ppm		
Remark	Possibility of significant uptake through the skin		
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	307 mg/m³ (mixed isomers)		
	50 ppm (mixed isomers)		
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)		
	100 ppm (isomers mixtures)		
OEL chemical category	Skin notation		
Belgium - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Skin, Skin notation		
Bulgaria - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
Croatia - Occupational Exposure Limits			
GVI (OEL TWA)	308 mg/m³		
	50 ppm		
OEL chemical category	Skin notation		
Cyprus - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Skin-potential for cutaneous absorption		

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
Czech Republic - Occupational Exposure Limits			
PEL (OEL TWA)	270 mg/m³		
OEL chemical category	Potential for cutaneous absorption		
Denmark - Occupational Exposure Limits			
OEL TWA	309 mg/m³		
	50 ppm		
OEL STEL	618 mg/m³		
	100 ppm		
OEL chemical category	Potential for cutaneous absorption		
Estonia - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Skin notation		
Finland - Occupational Exposure Limits			
HTP (OEL TWA)	310 mg/m³		
	50 ppm		
OEL chemical category	Potential for cutaneous absorption		
France - Occupational Exposure Limits			
VME (OEL TWA)	308 mg/m³ (restrictive limit)		
VIME (GEE TVVA)	50 ppm (restrictive limit)		
OEL chemical category	Risk of cutaneous absorption		
Germany - Occupational Exposure Limits (TRGS 900)  AGW (OEL TWA) 310 mg/m³ (isomer mixture)			
AGW (OEL TWA)			
50 ppm (isomer mixture)			
Gibraltar - Occupational Exposure Limits	Table 1 a		
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Skin notation		
Greece - Occupational Exposure Limits			
OEL TWA	600 mg/m³		
	100 ppm		
OEL STEL	900 mg/m³		
	150 ppm		
OEL chemical category	skin - potential for cutaneous absorption		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	308 mg/m³		
Ireland - Occupational Exposure Limits			
	1		
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)propanol)		

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)		
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)		
OEL chemical category	Potential for cutaneous absorption		
Italy - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	skin - potential for cutaneous absorption		
Latvia - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	skin - potential for cutaneous exposure		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)		
	50 ppm (2-(2-Methoxypropoxy)-propanol)		
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)		
	75 ppm (2-(2-Methoxypropoxy)-propanol)		
OEL chemical category	Skin notation		
Luxembourg - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Possibility of significant uptake through the skin		
Malta - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Possibility of significant uptake through the skin		
Netherlands - Occupational Exposure Limits			
TGG-8u (OEL TWA)	300 mg/m³		
	48.7 ppm		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)		
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)		
Portugal - Occupational Exposure Limits	•		
OEL TWA	308 mg/m³ (indicative limit value)		
	50 ppm (indicative limit value)		
OEL STEL	150 ppm		
OEL chemical category	skin - potential for cutaneous exposure indicative limit value		
Romania - Occupational Exposure Limits	•		
OEL TWA	308 mg/m³		
	-		

# Safety Data Sheet

OEL chemical category         Skin notation           OEL chemical category         Skin notation           NPHY (OEL TWA)         308 mg/m²           50 ppm         OEL chemical category           OEL TWA         308 mg/m²           Stovenia - Occupational Exposure Limits         50 ppm           OEL TWA         308 mg/m²           50 ppm         90 mg/m²           60 ppm         90 mg/m²           60 ppm         90 ppm           OEL chemical category         90 mg/m²           Spain - Occupational Exposure Limits         ************************************	Dipropylene glycol monomethyl ether (34590-94-8)		
Slovakia - Occupational Exposure Limits           NPHV (OEL TWA)         308 mg/m²           50 ppm         Potential for cutaneous absorption           Slovania - Occupational Exposure Limits           OEL TWA         308 mg/m²           50 ppm         50 ppm           OEL STEL         308 mg/m²           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)           308 mg/m² (indicative limit value)           OEL chemical category         80 mg/m² (indicative limit value)           Sweden - Occupational Exposure Limits           Nove (OEL TWA)           300 mg/m²           50 ppm           KGY (OEL TWA)           400 mg/m²           50 ppm           KGY (OEL TWA)           50 ppm           KGY (OEL TWA)           60 mg/m²           75 ppm           OEL chemical category         80 mg/m²           WEL TWA (OEL TWA)         308 mg/m²           50 ppm           WEL STEL (OEL STEL)         24 mg/m² (calculated)           60 ppm           Norway - Occupational		50 ppm	
NPHV (DEL TWA)         30 mg/m²           50 ppm           OEL chemical category         Potential for cutaneous absorption           Stovenia - Occupational Exposure Limits           OEL TWA         308 mg/m³           50 ppm           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           Spain - Occupational Exposure Limits           VMS (OEL TWA)         300 mg/m²           Spain - Occupational Exposure Limits           VMS (OEL STEL)         450 mg/m²           OEL chemical category         8kin notation           VMS (OEL TWA)         308 mg/m²           OEL chemical category         8kin notation           VME TWA (OEL TWA)         308 mg/m²         30 mg/m²           VMS (OEL TWA)         308 mg/m²         30 mg/m²           VMS (OEL TWA)         300 mg/m² (accudated)         300 mg/m² (accudated)           VMS (OEL TWA)         300 mg/m² (accudated)	OEL chemical category	Skin notation	
DEL chemical category         Potential for cutaneous absorption           Stovenia - Occupational Exposure Limits           DEL TWA         308 mg/m³           50 ppm         50 ppm           OEL STEL         308 mg/m³           50 ppm         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         VLA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           OEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits         300 mg/m³           KGY (OEL TWA)         300 mg/m³           50 ppm         450 mg/m³           KGY (OEL STEL)         450 mg/m³           CEL chemical category         Skin notation           United Kingdom - Occupational Exposure Limits         Skin notation           WEL TWA (OEL TWA)         308 mg/m³           50 ppm           WEL STEL (OEL STEL)         924 mg/m² (calculated)           150 ppm (calculated)           WEL STEL (OEL STEL)         924 mg/m² (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits         Sp ppm (calculated)           Kortidasverdi (OEL TWA)         300 mg/m	Slovakia - Occupational Exposure Limits		
OEL chemical category         Potential for cutaneous absorption           Slovenia - Occupational Exposure Limits           OEL TWA         308 mg/m²           50 ppm         50 ppm           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         308 mg/m² (indicative limit value)           VLA-ED (OEL TWA)         308 mg/m² (indicative limit value)           50 ppm (indicative limit value)         50 ppm (indicative limit value)           Sweden - Occupational Exposure Limits         50 ppm (indicative limit value)           Sweden - Occupational Exposure Limits         50 ppm (indicative limit value)           KGY (OEL STEL)         450 mg/m²           KGY (OEL STEL)         450 mg/m²           KGY (OEL STEL)         450 mg/m²           WEL TWA (OEL TWA)         308 mg/m²           50 ppm         50 ppm           WEL TWA (OEL TWA)         308 mg/m²           50 ppm         50 ppm           WEL STEL (OEL STEL)         924 mg/m² (calculated)           WEL chemical category         924 mg/m² (calculated)           WEL chemical category         90 ppm (aerosel value)           Kortidsverid (OEL TWA)         300 mg/m² (aerosel value)           Fo ppm (value calculated)         75 p	NPHV (OEL TWA)	308 mg/m³	
Slovenia - Occupational Exposure Limits		50 ppm	
OEL TWA         308 mg/m²           50 ppm         50 ppm           OEL STEL         308 mg/m²           50 ppm         50 ppm           OEL chemical category         Potential for cutaneous absorption           VIA-ED (OEL TWA)         308 mg/m² (indicative limit value)           50 ppm (indicative limit value)         50 ppm (indicative limit value)           OEL chemical category         skin - potential for cutaneous absorption           Swedon - Occupational Exposure Limits         450 mg/m²           50 ppm         50 ppm           KGV (OEL STEL)         450 mg/m²           75 ppm         60 ppm           OEL chemical category         5kin notation           United Kingdom - Occupational Exposure Limits         75 ppm           WEL STEL (OEL STEL)         308 mg/m²           50 ppm           WEL STEL (OEL STEL)         924 mg/m² (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits           Grenseverdi (OEL TWA)         300 mg/m²           50 ppm           Kortidsverdi (OEL STEL)         375 mg/m² (value calculated)           75 ppm (value calculated)           75	OEL chemical category	Potential for cutaneous absorption	
S0 ppm   S0 ppm (indicative limit value)   S0 ppm	Slovenia - Occupational Exposure Limits		
OEL STEL         308 mg/m³           50 ppm         Potentical category           Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           50 ppm (indicative limit value)         50 ppm (indicative limit value)           Sweden - Occupational Exposure Limits           NGY (OEL TWA)           300 mg/m³           50 ppm           KGY (OEL STEL)           450 mg/m³           75 ppm           OEL chemical category         Skin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA)         308 mg/m³           50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits           Kortfideverdi (OEL TWA)         300 mg/m³           50 ppm         50 ppm           Kortfideverdi (OEL STEL)         375 mg/m² (value calculated)           Type (value calculated)           75 ppm (value calculated)         75 ppm (value calculated)           Type (v	OEL TWA	308 mg/m³	
So ppm   So ppm		50 ppm	
OEL chemical category     Potential for cutaneous absorption       Spain - Occupational Exposure Limits       VLA-ED (OEL TWA)     308 mg/m³ (indicative limit value)       OEL chemical category     skin - potential for cutaneous absorption       Sweden - Occupational Exposure Limits       NGY (OEL TWA)     300 mg/m³       50 ppm       KGV (OEL STEL)     400 mg/m³       75 ppm     75 ppm       OEL chemical category     Skin notation       United Kingdom - Occupational Exposure Limits       WEL TWA (OEL TWA)     308 mg/m³       50 ppm       WEL STEL (OEL STEL)     924 mg/m³ (calculated)       WEL steenical category     Potential for cutaneous absorption       Norway - Occupational Exposure Limits       Grenseverdi (OEL TWA)     300 mg/m³       50 ppm       Korttideverdi (OEL STEL)     300 mg/m³ (value calculated)       For pym² (value calculated)     75 ppm (value calculated)       OEL chemical category     Skin notation       Switzeriand - Occupational Exposure Limits       MAK (OEL TWA)     300 mg/m³ (aerosol, vapour)       KZGW (OEL STEL)     300 mg/m³ (aerosol, vapour)	OEL STEL	308 mg/m³	
Spain - Occupational Exposure Limits   VLA-ED (OEL TWA)		50 ppm	
VLA-ED (OEL TWA)  308 mg/m³ (indicative limit value)  50 ppm (indicative limit value)  Seeden - Occupational Exposure Limits  NGV (OEL TWA)  300 mg/m³  50 ppm  KGV (OEL STEL)  450 mg/m³  75 ppm  OEL chemical category  Skin notation  United Kingdom - Occupational Exposure Limits  WEL TWA (OEL STEL)  400 mg/m³  50 ppm  WEL STEL (OEL STEL)  201 mg/m³ (calculated)  150 ppm (calculated)  150 ppm (calculated)  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  308 mg/m³  50 ppm  Kortidisverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm  Coel chemical category  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Kortidisverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	OEL chemical category	Potential for cutaneous absorption	
So ppm (indicative limit value)	Spain - Occupational Exposure Limits	•	
OEL chemical category     skin - potential for cutaneous absorption       Sweden - Occupational Exposure Limits       NGV (OEL TWA)     300 mg/m³       50 ppm       KGV (OEL STEL)     450 mg/m³       75 ppm     75 ppm       OEL chemical category     Skin notation       United Kingdom - Occupational Exposure Limits       WEL TWA (OEL TWA)     308 mg/m³       50 ppm       WEL STEL (OEL STEL)     924 mg/m³ (calculated)       WEL chemical category     Potential for cutaneous absorption       Norway - Occupational Exposure Limits       Genseverdi (OEL TWA)     300 mg/m³       50 ppm       Korttidsverdi (OEL STEL)     375 mg/m³ (value calculated)       75 ppm (value calculated)       OEL chemical category     Skin notation       Switzerland - Occupational Exposure Limits       MAK (OEL TWA)     300 mg/m³ (aerosol, vapour)       50 ppm (aerosol, vapour)       KZGW (OEL STEL)     300 mg/m³ (aerosol, vapour)	VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)	
NGV (OEL TWA)    So mg/m³     50 ppm     KGV (OEL STEL)     A50 mg/m³     75 ppm     OEL chemical category     Skin notation		50 ppm (indicative limit value)	
NGV (OEL TWA)         300 mg/m³           50 ppm         450 mg/m³           KGV (OEL STEL)         450 mg/m³           75 ppm         75 ppm           OEL chemical category         Skin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA)         308 mg/m³           50 ppm         50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits         300 mg/m³           Grenseverdi (OEL TWA)         300 mg/m³           Korttidsverdi (OEL STEL)         375 mg/m³ (value calculated)           To ppm (value calculated)         75 ppm (value calculated)           OEL chemical category         Skin notation           Switzerland - Occupational Exposure Limits           MAK (OEL TWA)         300 mg/m³ (aerosol, vapour)           KZGW (OEL STEL)         300 mg/m³ (aerosol, vapour)	OEL chemical category	skin - potential for cutaneous absorption	
KGV (OEL STEL)  450 mg/m³ 75 ppm  OEL chemical category Skin notation  United Kingdom - Occupational Exposure Limits  WEL TWA (OEL TWA)  50 ppm  WEL STEL (OEL STEL)  424 mg/m³ (calculated) 750 ppm  WEL chemical category Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	Sweden - Occupational Exposure Limits		
KGV (OEL STEL)  450 mg/m³ 75 ppm  OEL chemical category  Skin notation  United Kingdom - Occupational Exposure Limits  WEL TWA (OEL TWA)  50 ppm  WEL STEL (OEL STEL)  924 mg/m³ (calculated) 150 ppm (calculated) 150 ppm (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)	NGV (OEL TWA)	300 mg/m³	
OEL chemical category Skin notation  United Kingdom - Occupational Exposure Limits  WEL TWA (OEL TWA)  308 mg/m³ 50 ppm  WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated)  WEL chemical category Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm  Korttidsverdi (OEL STEL) 375 mg/m² (value calculated) 75 ppm (value calculated)  OEL chemical category Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) 300 mg/m³ (aerosol, vapour)  KZGW (OEL STEL) 300 mg/m³ (aerosol, vapour)		50 ppm	
OEL chemical category  United Kingdom - Occupational Exposure Limits  WEL TWA (OEL TWA)  Below Fig. 1  WEL STEL (OEL STEL)  WEL STEL (OEL STEL)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  WEL chemical Category  Norway - Occupational Exposure Limits  Grenseverdi (OEL STEL)  WEL chemical category  Since the state of t	KGV (OEL STEL)	450 mg/m³	
United Kingdom - Occupational Exposure Limits  WEL TWA (OEL TWA)  308 mg/m³ 50 ppm  WEL STEL (OEL STEL)  924 mg/m³ (calculated)  150 ppm (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³ 50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)		75 ppm	
WEL TWA (OEL TWA)  308 mg/m³ 50 ppm  WEL STEL (OEL STEL)  924 mg/m³ (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³ 50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	OEL chemical category	Skin notation	
WEL STEL (OEL STEL)  924 mg/m³ (calculated)  150 ppm (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	United Kingdom - Occupational Exposure Limits		
WEL STEL (OEL STEL)  924 mg/m³ (calculated)  150 ppm (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	WEL TWA (OEL TWA)	308 mg/m³	
150 ppm (calculated)   WEL chemical category   Potential for cutaneous absorption   Norway - Occupational Exposure Limits   300 mg/m³   50 ppm		50 ppm	
WEL chemical category  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  So ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	WEL STEL (OEL STEL)	924 mg/m³ (calculated)	
Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  50 ppm  Korttidsverdi (OEL STEL)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)		150 ppm (calculated)	
Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	WEL chemical category	Potential for cutaneous absorption	
Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated) 75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	Norway - Occupational Exposure Limits		
Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)  OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	Grenseverdi (OEL TWA)	300 mg/m³	
75 ppm (value calculated)  OEL chemical category Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) 300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL) 300 mg/m³ (aerosol, vapour)		50 ppm	
OEL chemical category  Skin notation  Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)	
Switzerland - Occupational Exposure Limits  MAK (OEL TWA)  300 mg/m³ (aerosol, vapour)  50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)		75 ppm (value calculated)	
MAK (OEL TWA)         300 mg/m³ (aerosol, vapour)           50 ppm (aerosol, vapour)           KZGW (OEL STEL)         300 mg/m³ (aerosol, vapour)	OEL chemical category	Skin notation	
50 ppm (aerosol, vapour)  KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	Switzerland - Occupational Exposure Limits	•	
KZGW (OEL STEL)  300 mg/m³ (aerosol, vapour)	MAK (OEL TWA)	300 mg/m³ (aerosol, vapour)	
		50 ppm (aerosol, vapour)	
50 ppm (aerosol, vapour)	KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)	
		50 ppm (aerosol, vapour)	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
USA - ACGIH - Occupational Exposure Limits	USA - ACGIH - Occupational Exposure Limits		
ACGIH® TLV® TWA	50 ppm (Dipropylene glycol methyl ether)		
Toluene (108-88-3)			
EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA	192 mg/m³		
	50 ppm		
IOEL STEL	384 mg/m³		
	100 ppm		
Remark	Possibility of significant uptake through the skin		
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	190 mg/m³		
	50 ppm		
MAK (OEL STEL)	380 mg/m³		
	100 ppm		
OEL chemical category	Skin notation		
Belgium - Occupational Exposure Limits			
OEL TWA	77 mg/m³		
	20 ppm		
OEL STEL	384 mg/m³		
	100 ppm		
OEL chemical category	Skin, Skin notation		
Bulgaria - Occupational Exposure Limits			
OEL TWA	192 mg/m³		
	50 ppm		
OEL STEL	384 mg/m³		
	100 ppm		
Bulgaria - Biological limit values			
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift		
Croatia - Occupational Exposure Limits			
GVI (OEL TWA)	192 mg/m³		
	50 ppm		
KGVI (OEL STEL)	384 mg/m³		
	100 ppm		
OEL chemical category	Skin notation		

# Safety Data Sheet

Toluene (108-88-3)	
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m³
OEL chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis)  1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)  1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis)  1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m³
	25 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m³

# Safety Data Sheet

Toluene (108-88-3)			
	25 ppm		
HTP (OEL STEL)	380 mg/m³		
	100 ppm		
OEL chemical category	Potential for cutaneous absorption		
Finland - Biological limit values			
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day		
France - Occupational Exposure Limits			
VME (OEL TWA)	76.8 mg/m³ (restrictive limit)		
	20 ppm (restrictive limit)		
VLE (OEL C/STEL)	384 mg/m³ (restrictive limit)		
	100 ppm (restrictive limit)		
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption		
France - Biological limit values			
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)		
Germany - Occupational Exposure Limits (TRGS 90	00)		
AGW (OEL TWA)	190 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
Chemical category	Skin notation		
Germany - Biological limit values (TRGS 903)			
Biological limit value	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 μg/l Parameter: Toluene - Medium: urine - Sampling time: end of exposure or shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: at the end of the shift, in case of long-term exposure after several previous shifts		
Gibraltar - Occupational Exposure Limits			
OEL TWA	192 mg/m³		
	50 ppm		
OEL STEL	384 mg/m³		
	100 ppm		
OEL chemical category	Skin notation		
Greece - Occupational Exposure Limits	Greece - Occupational Exposure Limits		
OEL TWA	192 mg/m³		
	50 ppm		
OEL STEL	384 mg/m³		
	100 ppm		
OEL chemical category	skin - potential for cutaneous absorption		

# Safety Data Sheet

Toluene (108-88-3)	
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	190 mg/m³
CK (OEL STEL)	384 mg/m³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m³
	14 ppm
OEL chemical category	skin - potential for cutaneous exposure
Latvia - Biological Exposure Indices	
BEI	600 μg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of exposure (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 75 μg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: at the end of exposure or shift (after hydrolysis)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m³
	50 ppm
TPRV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Reproductive toxin, Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
L	I.

# Safety Data Sheet

Toluene (108-88-3)	
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m³
NDSCh (OEL STEL)	200 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	384 mg/m³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m³
	50 ppm
NPHV (OEL C)	384 mg/m³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work
	shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift

# Safety Data Sheet

Toluene (108-88-3)		
Slovenia - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Category 2, Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	192 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Spain - Biological limit values		
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	192 mg/m³	
	50 ppm	
KGV (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	191 mg/m³	
	50 ppm	
WEL STEL (OEL STEL)	384 mg/m³	
	100 ppm	
WEL chemical category	Potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	94 mg/m³	
	25 ppm	
Korttidsverdi (OEL STEL)	141 mg/m³ (value calculated)	
	37.5 ppm (value calculated)	
OEL chemical category	Skin notation	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	190 mg/m³	
	50 ppm	
KZGW (OEL STEL)	760 mg/m³	
	200 ppm	

# Safety Data Sheet

Toluene (108-88-3)	
OEL chemical category	Skin notation, Category 2 reproductive toxin
Switzerland - BAT	
BAT	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 μmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 μmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 μg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	20 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Acetyl Propionyl (600-14-6)	
Germany - Occupational Exposure Limits (TRGS 90	00)
AGW (OEL TWA)	0.083 mg/m³
	0.02 ppm
Chemical category	Skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	0.083 mg/m³
	0.02 ppm
OEL STEL	0.083 mg/m³
	0.02 ppm
OEL chemical category	Potential for cutaneous absorption
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	0.08 mg/m³
	0.02 ppm
KZGW (OEL STEL)	0.16 mg/m³
	0.04 ppm
OEL chemical category	Sensitizer, Skin notation
benzaldehyde (100-52-7)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m³

# Safety Data Sheet

benzaldehyde (100-52-7)		
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	4.4 mg/m³	
	1 ppm	
HTP (OEL C)	17.4 mg/m³	
	4 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³	
CK (OEL STEL)	10 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	40 mg/m³	
benzyl alcohol (100-51-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	40 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	45 mg/m³	
	10 ppm	
Germany - Occupational Exposure Limits (TRGS 90	00)	
AGW (OEL TWA)	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
OEL chemical category	Skin notation	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	22 mg/m³	
	5 ppm	

# Safety Data Sheet

benzyl alcohol (100-51-6)		
OEL STEL	44 mg/m³	
	10 ppm	
OEL chemical category	Potential for cutaneous absorption	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	22 mg/m³ (aerosol, vapour)	
	5 ppm (aerosol, vapour)	
OEL chemical category	Skin notation	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-	5)	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	140 mg/m³	
	25 ppm	
HTP (OEL STEL)	280 mg/m³	
	50 ppm	
Germany - Occupational Exposure Limits (TRGS 90	00)	
AGW (OEL TWA)	28 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation, Skin sensitization	
Slovenia - Occupational Exposure Limits		
OEL TWA	28 mg/m³	
	5 ppm	
OEL STEL	112 mg/m³	
	20 ppm	
OEL chemical category	Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	168 mg/m³	
	30 ppm	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	140 mg/m³	
	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
	37.5 ppm (value calculated)	
OEL chemical category	Allergenic substance	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	40 mg/m³	
	7 ppm	
KZGW (OEL STEL)	80 mg/m³	
, ,	-	

# Safety Data Sheet

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)			
	14 ppm		
OEL chemical category	Sensitizer		
.betaPinene (127-91-3)			
Belgium - Occupational Exposure Limits			
OEL TWA	20 ppm		
Estonia - Occupational Exposure Limits			
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)		
	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)		
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)		
	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	150 mg/m³		
	25 ppm		
TPRV (OEL STEL)	300 mg/m³		
	50 ppm		
Portugal - Occupational Exposure Limits			
OEL TWA	20 ppm (Turpentine and selected Monoterpenes)		
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA)	113 mg/m³		
	20 ppm		
OEL chemical category	Sensitizer		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	150 mg/m³		
	25 ppm		
KGV (OEL STEL)	300 mg/m³		
	50 ppm		
OEL chemical category	Skin sensitizer		
Norway - Occupational Exposure Limits	Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	140 mg/m³		
	25 ppm		
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)		
	37.5 ppm (value calculated)		
USA - ACGIH - Occupational Exposure Lim	its		
ACGIH® TLV® TWA	20 ppm (Turpentine and selected Monoterpenes)		
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer		

# Safety Data Sheet

.alphaPinene (80-56-8)	
Belgium - Occupational Exposure Limits	
OEL TWA	20 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	150 mg/m³
	25 ppm
TPRV (OEL STEL)	300 mg/m³
	50 ppm
Portugal - Occupational Exposure Limits	
OEL TWA	20 ppm (Turpentine and selected Monoterpenes)
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	113 mg/m³
	20 ppm
OEL chemical category	Sensitizer
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	150 mg/m³
	25 ppm
KGV (OEL STEL)	300 mg/m³
	50 ppm
OEL chemical category	Skin sensitizer
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	140 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	20 ppm (Turpentine and selected Monoterpenes)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

p-Cymene (99-87-6)		
Denmark - Occupational Exposure Limits		
OEL TWA	135 mg/m³ (Methylisopropylbenzenes)	
	25 ppm (Methylisopropylbenzenes)	
OEL STEL	270 mg/m³ (Methylisopropylbenzenes)	
	50 ppm (Methylisopropylbenzenes)	
Estonia - Occupational Exposure Limits		
OEL TWA	140 mg/m³	
	25 ppm	
OEL STEL	190 mg/m³	
	35 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	10 mg/m³ (Cymene (2, 3, 4-isomers mixture))	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	140 mg/m³	
	25 ppm	
TPRV (OEL STEL)	190 mg/m³	
	35 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	140 mg/m³	
	25 ppm	
KGV (OEL STEL)	190 mg/m³	
	35 ppm	

### 8.2. Exposure controls

### Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### **Personal protection equipment**

#### Personal protective equipment symbol(s):





#### Eye and face protection

#### Eye protection:

Chemical goggles or safety glasses. Safety glasses

#### Skin protection

### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear protective gloves.

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **Respiratory protection**

#### Respiratory protection:

Wear appropriate mask

#### **Environmental exposure controls**

#### **Environmental exposure controls:**

Avoid release to the environment.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : light yellow. amber. Conforms to standard.

Odour : characteristic. characteristic.

: Not available Odour threshold : Not applicable Melting point Freezing point : Not available Boiling point : Not available Flammability : Not applicable Lower explosion limit : Not available Upper explosion limit : Not available Flash point : > 95 °C Auto-ignition temperature : Not available Decomposition temperature : Not available : Not available : Not available Viscosity, kinematic : Not available Solubility Partition coefficient n-octanol/water (Log Kow) Not available

Vapour pressure : 0.001378235 mm Hg (calculated value)

Vapour pressure at  $50^{\circ}$ C : Not available Density : Not available Relative density :  $\approx 1.109$  Relative vapour density at  $20^{\circ}$ C : Not available Particle characteristics : Not applicable

#### 9.2. Other information

Other safety characteristics

VOC content : 4.70118875 % (calculated value)(CARB VOC) (%w/w)

#### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

No additional information available

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation) :	Not classified	
PUMPKIN PIE #EU13513F		
ATE CLP (oral)	809.96 mg/kg bodyweight	
benzyl benzoate (120-51-4)		
LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)	
LD50 oral	1160 mg/kg bodyweight	
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)	
Cinnamic aldehyde (104-55-2)		
LD50 oral rat	2220 mg/kg (Source: NLM_CIP)	
LD50 oral	2220 mg/kg	
LD50 dermal rabbit	1260 mg/kg (Source: EPA_HPV)	
LD50 dermal	1260 mg/kg	
Eugenol (97-53-0)		
LD50 oral rat	1930 mg/kg (Source: NZ_CCID)	
LD50 oral	2500 mg/kg bodyweight	
LC50 Inhalation - Rat	> 2.58 mg/l/4h	
Ethyl vanillin (121-32-4)		
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)	
LD50 oral	3000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
COUMARIN (91-64-5)		
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rat	293 mg/kg (Source: ECHA_API)	
Phenylethyl alcohol (60-12-8)		
LD50 oral rat	1609 mg/kg (Source: EPA_HPV)	
LD50 oral	1610 mg/kg	
LD50 dermal rabbit	2535 mg/kg (Source: EPA_HPV)	
LC50 Inhalation - Rat	> 4.63 mg/l/4h	
Terpineol (8000-41-7)		
LD50 oral rat	2900 mg/kg (Source: IUCLID)	
LD50 oral	4300 mg/kg bodyweight	
LD50 dermal rabbit	> 3000 mg/kg (Source: IUCLID)	

# Safety Data Sheet

Anisic aldehyde (123-11-5)		
LD50 oral rat	3210 mg/kg (Source: ECHA)	
LD50 oral	3210 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)	
LC50 Inhalation - Rat	> 0.32 mg/l (Exposure time: 7 h Source: ECHA)	
Ethyl maltol (4940-11-8)		
LD50 oral rat	1150 mg/kg (Source: NLM_CIP)	
LD50 oral	1200 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)	
Amyl cinnamic aldehyde (122-40-7)		
LD50 oral rat	3730 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 2000 mg/kg (Source: CHEMVIEW)	
Veratryl aldehyde (Veratraldehyde) (120-14-9)		
LD50 oral rat	2 g/kg (Source: NLM_CIP)	
LD50 oral	2000 mg/kg bodyweight	
Dipropylene glycol monomethyl ether (34590-	94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)	
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)	
Toluene (108-88-3)		
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)	
LC50 Inhalation - Rat	12.5 mg/l/4h	
Acetyl Propionyl (600-14-6)		
LD50 oral rat	3 g/kg (Source: NLM_CIP)	
LD50 oral	3000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg (Source: NIOSH)	
1,2-Cyclopentanedione, 3-methyl- (765-70-8)		
LD50 oral	1067 mg/kg bodyweight	
benzaldehyde (100-52-7)		
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)	
LC50 Inhalation - Rat	< 5 mg/l/4h	
benzyl alcohol (100-51-6)		
LD50 oral rat	1230 mg/kg (Source: NLM_CIP)	
LD50 oral	1570 mg/kg	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)		
LD50 oral rat	4400 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)	

# Safety Data Sheet

.betaPinene (127-91-3)	
LD50 oral rat	> 5000 mg/kg (Source: EPA_HPV)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
.alphaPinene (80-56-8)	
LD50 oral rat	3700 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 5000 mg/kg (Source: CHEMVIEW)
p-Cymene (99-87-6)	
LD50 oral rat	4750 mg/kg (Source: NLM_CIP)
LD50 oral	4750 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
LC50 Inhalation - Rat	> 9.7 mg/l (Exposure time: 5 h Source: EU_CLH)
LC50 Inhalation - Rat (Vapours)	9.7 mg/l/4h
Skin corrosion/irritation : Serious eye damage/irritation : Respiratory or skin sensitisation :	Causes serious eye irritation.  May cause an allergic skin reaction.
Germ cell mutagenicity : Carcinogenicity :	Not classified Not classified
Eugenol (97-53-0)	The state and th
IARC group	3 - Not classifiable
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Toluene (108-88-3)	
IARC group	3 - Not classifiable
(R)-p-mentha-1,8-diene; d-limonene (5989-27	-5)
IARC group	3 - Not classifiable
•	Not classified
STOT-single exposure :	Not classified
benzaldehyde (100-52-7)	1
STOT-single exposure STOT-repeated exposure :	May cause respiratory irritation.  Not classified
Acetyl Propionyl (600-14-6)	Not classified
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard :	Not classified
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s
Toluene (108-88-3)	
Hydrocarbon	Yes
(R)-p-mentha-1,8-diene; d-limonene (5989-27-	-5)
Hydrocarbon	Yes

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.betaPinene (127-91-3)		
Hydrocarbon	Yes	
.alphaPinene (80-56-8)		
Hydrocarbon Yes		
beta-Caryophyllene (87-44-5)		
Hydrocarbon Yes		
p-Cymene (99-87-6)		
Hydrocarbon Yes		

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Very toxic to aquatic life.

(acute)

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

citionic)		
benzyl benzoate (120-51-4)		
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
NOEC (chronic)	0.168 mg/l	
Eugenol (97-53-0)		
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
Ethyl vanillin (121-32-4)		
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
Phenylethyl alcohol (60-12-8)		
EC50 - Crustacea [1]	287.17 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	490 mg/l (Species: Desmodesmus subspicatus)	
Ethyl maltol (4940-11-8)		
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)	
Dipropylene glycol monomethyl ether (34590-94-8)		
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Toluene (108-88-3)		
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

# Safety Data Sheet

Toluene (108-88-3)

Toluelle (100-00-3)		
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])	
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)	
benzaldehyde (100-52-7)		
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)	
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)	
benzyl alcohol (100-51-6)		
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-	5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)	
.alphaPinene (80-56-8)		
LC50 - Fish [1]	0.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)	
EC50 - Crustacea [1]	41 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
12.2. Persistence and degradability		
PUMPKIN PIE #EU13513F		
Persistence and degradability	Rapidly degradable	
benzyl benzoate (120-51-4)		
Persistence and degradability	May cause long-term adverse effects in the environment.	
Cinnamic aldehyde (104-55-2)		
Persistence and degradability	Rapidly degradable	
Eugenol (97-53-0)		
Persistence and degradability	Rapidly degradable	
Ethyl vanillin (121-32-4)		
Persistence and degradability	Not established.	
COUMARIN (91-64-5)		
Persistence and degradability	Rapidly degradable	
Phenylethyl alcohol (60-12-8)		
Persistence and degradability	Rapidly degradable	
Terpineol (8000-41-7)		
Persistence and degradability	Rapidly degradable	
Anisic aldehyde (123-11-5)		
Persistence and degradability	Rapidly degradable	

# Safety Data Sheet

Ethyl maltol (4940-11-8)		
Persistence and degradability	Rapidly degradable	
Amyl cinnamic aldehyde (122-40-7)		
Persistence and degradability	Rapidly degradable	
Veratryl aldehyde (Veratraldehyde) (120-14-9)		
Persistence and degradability	Rapidly degradable	
Dipropylene glycol monomethyl ether (34590	-94-8)	
Persistence and degradability	Rapidly degradable	
Toluene (108-88-3)		
Persistence and degradability	Rapidly degradable	
Acetyl Propionyl (600-14-6)		
Persistence and degradability	Rapidly degradable	
1,2-Cyclopentanedione, 3-methyl- (765-70-8)		
Persistence and degradability	Rapidly degradable	
benzaldehyde (100-52-7)		
Persistence and degradability	Rapidly degradable	
benzyl alcohol (100-51-6)		
Persistence and degradability	Rapidly degradable	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-	5)	
Persistence and degradability	Rapidly degradable	
.betaPinene (127-91-3)		
Persistence and degradability	Rapidly degradable	
.alphaPinene (80-56-8)		
Persistence and degradability	Rapidly degradable	
beta-Caryophyllene (87-44-5)		
Persistence and degradability	Rapidly degradable	
p-Cymene (99-87-6)		
Persistence and degradability	Rapidly degradable	
12.3. Bioaccumulative potential		
benzyl benzoate (120-51-4)		
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)	
Bioaccumulative potential	Not established.	
Cinnamic aldehyde (104-55-2)		
Partition coefficient n-octanol/water (Log Pow)	2.1065 (at 25 °C)	
Eugenol (97-53-0)		
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5)	

# Safety Data Sheet

Ethyl vanillin (121-32-4)		
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)	
Bioaccumulative potential	Not established.	
COUMARIN (91-64-5)		
Partition coefficient n-octanol/water (Log Pow)	≥ 1.91 – ≤ 1.51 (at 25 °C (at pH 7)	
Phenylethyl alcohol (60-12-8)		
Partition coefficient n-octanol/water (Log Pow)	1.36 (at 20 °C (at pH 7)	
Anisic aldehyde (123-11-5)		
Partition coefficient n-octanol/water (Log Pow)	1.56 (at 25 °C (at pH >7.9-<8.25)	
Ethyl maltol (4940-11-8)		
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 25 °C)	
Amyl cinnamic aldehyde (122-40-7)		
Partition coefficient n-octanol/water (Log Pow)	2.498 (at 25 °C (at pH 6.2)	
Veratryl aldehyde (Veratraldehyde) (120-14-9)		
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 25 °C)	
Dipropylene glycol monomethyl ether (34590-	94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)	
Toluene (108-88-3)		
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)	
1,2-Cyclopentanedione, 3-methyl- (765-70-8)		
Partition coefficient n-octanol/water (Log Pow)	-0.54 (calculated value)	
benzaldehyde (100-52-7)		
BCF - Fish [1]	(no significant bioaccumulation)	
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)	
benzyl alcohol (100-51-6)		
Partition coefficient n-octanol/water (Log Pow)	1.05	
(R)-p-mentha-1,8-diene; d-limonene (5989-27-	5)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2)	
.betaPinene (127-91-3)		
Partition coefficient n-octanol/water (Log Pow)	4.4 (at 25 °C)	
.alphaPinene (80-56-8)		
Partition coefficient n-octanol/water (Log Pow)	4.1	
beta-Caryophyllene (87-44-5)		
Partition coefficient n-octanol/water (Log Pow)	6.23 (at 25 °C (at pH 7)	
p-Cymene (99-87-6)		
Partition coefficient n-octanol/water (Log Pow)	4.8 (at 20 °C (at pH 7)	
Partition coefficient n-octanol/water (Log Kow)	0	

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

benzyl benzoate (120-51-4)	
Other information Avoid release to the environment.	
Ethyl vanillin (121-32-4)	
Other information Avoid release to the environment.	

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shippin	g name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate)
Transport document descr	iption			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate), 9, III
14.3. Transport hazard	14.3. Transport hazard class(es)			
9	9	9	9	9

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
**************************************	**************************************	**************************************	**************************************	**************************************
14.4. Packing group	14.4. Packing group			
III	III	III	III	III
14.5. Environmental haz	zards			
Dangerous for the environment: Yes  Marine pollutant: Yes  EmS-No. (Spillage): S-F  Dangerous for the environment: Yes  Dangerous for the environment: Yes  environment: Yes  Ens-No. (Spillage): S-F				
No supplementary information available				

#### 14.6. Special precautions for user

#### **Overland transport**

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code (ADR) :

EAC code : •3Z

#### Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : LP01, P001 : PP1 Special packing provisions (IMDG) : IBC03 IBC packing instructions (IMDG) Tank instructions (IMDG) T4 : TP1. TP29 Tank special provisions (IMDG) Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 91

**Inland waterway transport** 

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU-Regulations**

#### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	ence code Applicable on Entry title or description	
3(a)	Acetyl Propionyl ; d- Limonene ; .alphaPinene ; .betaPinene ; p- Cymene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (	EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description	
3(b)	PUMPKIN PIE #EU13513F; Benzyl benzoate; Cinnamic aldehyde; Eugenol; Phenylethyl alcohol; Terpineol; Amyl cinnamic aldehyde; Benzaldehyde ; Acetyl Propionyl; Benzyl alcohol; d-Limonene; p- Cymene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	PUMPKIN PIE #EU13513F; Benzyl benzoate; Cinnamic aldehyde; Anisic aldehyde; Amyl cinnamic aldehyde; d-Limonene; p-Cymene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	
40.	Acetyl Propionyl ; d- Limonene ; .alphaPinene ; .betaPinene ; p- Cymene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

#### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

### VOC Directive (2004/42)

VOC content : 4.70118875 % (calculated value)(CARB VOC) (%w/w)

#### **Explosives Precursors Regulation (EU 2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### **Drug Precursors Regulation (EC 273/2004)**

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **National regulations**

#### **France**

Occupational diseases		
Code	Description	
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

#### Germany

VOC ordinance (ChemVOCFarbV) : VOC content : 4.70118875 % (calculated value)(CARB VOC)

(%w/w)

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

List of sensitizing substances (TRGS 907) : Contains sensitizing substances according TRGS 907.

Major Accidents Ordinance (12. BlmSchV) : Is not subject to the Major Accidents Ordinance (12. BlmSchV)

**Netherlands** 

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : Terpineol is listed

SZW-lijst van mutagene stoffen : Terpineol is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen –

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : Toluene is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

: None of the components are listed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

## 7/24/2025 (Revision date)

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **Poland**

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).

Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).

The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).

Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).

Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).

Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).

The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)

Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended). Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).

ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

#### **SECTION 16: Other information**

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	

# Safety Data Sheet

Abbreviations and acronyms:		
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disruptor	

Full text of H- and EUH-statements:		
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH208	Contains {0 message≤name of sensitising substance> fieldvalue=_SENSITIZER_COMPONENTS}. May produce an allergic reaction.	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Repr. 2	Reproductive toxicity, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1A	Skin sensitisation, category 1A	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H361	Suspected of damaging fertility or the unborn child.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.